

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Duftöl: Pear
UFI	: QK9P-ECQA-D00M-DEWY :
Product code	
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Professional use, Industrial use
Industrial/Professional use spec	: For professional use only Industrial
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Hansawax GmbH
Lloyd Industriepark
Richard-Dunkel-Straße 120
DE- 28199 Bremen
T 49-421-57890808
hallo@hansawax.de - www.hansawax.de

1.4. Emergency telephone number

Emergency number	: 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Suspected of damaging fertility or the unborn child. Toxic to aquatic life. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP)	: Warning
Contains	: Geranyl acetate; Eugenol; Cinnamic aldehyde; Neryl acetate; (R)-p-mentha-1,8-diene; d-limonene; Hexyl cinnamic aldehyde; Triplal (Vertocitral); Veratryl aldehyde (Veratraldehyde); COUMARIN
Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 - IF ON SKIN: Wash with plenty of water.
Extra phrases	: For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Verdorex	CAS-No.: 88-41-5 EC-No.: 201-828-7 REACH-no: 01-2119970713-33	3.7 – 7.3	Aquatic Chronic 2, H411
Geranyl acetate	CAS-No.: 105-87-3 EC-No.: 203-341-5 REACH-no: 01-2119973480-35	3.3 – 6.6	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802-33	2.8 – 5.5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-45	2.8 – 5.5	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
Neryl acetate	CAS-No.: 141-12-8 EC-No.: 205-459-2	1.5 – 2.9	Skin Sens. 1B, H317
Citronellyl acetate (mixed Isomers)	CAS-No.: 150-84-5 EC-No.: 205-775-0	1.2 – 2.4	Aquatic Chronic 2, H411 Skin Irrit. 2, H315

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
(R)-p-mentha-1,8-diene; d-limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 205-341-0 EC Index-No.: 601-096-00-2 REACH-no: 01-2119493353-35	0.9 – 1.8	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
2(3H)-Furanone, 5-heptyldihydro-	CAS-No.: 104-67-6 EC-No.: 203-225-4 REACH-no: 01-2119959333-34	0.9 – 1.7	Aquatic Chronic 3, H412
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0.8 – 1.66	Acute Tox. 4 (Oral), H302
isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.8 – 1.5	Flam. Liq. 2, H225 STOT SE 3, H336
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092-50	0.7 – 1.4	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314-33	0.7 – 1.3	Aquatic Chronic 2, H411
Butylated hydroxytoluene (BHT) crystals substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, ES, FI, FR, GB, GR, HR, IE, PT, SI, CH)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119480433-40	0.5 – 0.9	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Triplal (Vertocitral)	CAS-No.: 68039-49-6 EC-No.: 268-264-1	0.3 – 0.532	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408-32	0.2 – 0.4	Flam. Liq. 3, H226
Diphenyl oxide substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 101-84-8 EC-No.: 202-981-2 REACH-no: 01-2119472545-33	0.2 – 0.3	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Amyl formate substance with national workplace exposure limit(s) (LT, LV)	CAS-No.: 638-49-3 EC-No.: 211-340-6 EC Index-No.: 607-696-00-0	0.1 – 0.2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.1 – 0.2	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	0.1 – 0.1763	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Veratryl aldehyde (Veratraldehyde)	CAS-No.: 120-14-9 EC-No.: 204-373-2	0.075 – 0.125	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Alcohol C-10 substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.0114	Aquatic Chronic 3, H412
Aldehyde C-6 substance with national workplace exposure limit(s) (FI, PL)	CAS-No.: 66-25-1 EC-No.: 200-624-5	0 – 0.0028	Flam. Liq. 3, H226
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.000762 – 0.00127	Not classified
Caproic acid substance with national workplace exposure limit(s) (BG, LT, LV)	CAS-No.: 142-62-1 EC-No.: 205-550-7	0 – 0.0001	Eye Dam. 1, H318 Skin Corr. 1C, H314
butyric acid substance with national workplace exposure limit(s) (BG, LT, LV, RO)	CAS-No.: 107-92-6 EC-No.: 203-532-3 EC Index-No.: 607-135-00-X	0 – 0.0001	Skin Corr. 1B, H314
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.000015	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after eye contact	: If eye irritation persists: Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Suspected of damaging fertility or the unborn child. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: May cause an allergic skin reaction.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
Explosion hazard	: May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Precautions for safe handling : Ensure good ventilation of the work station. No open flames. No smoking. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep in fireproof place. Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store locked up. Store in a well-ventilated place. Keep cool.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Heat sources. Sources of ignition. Direct sunlight.
- Storage temperature : 25 °C
- Storage area : Store away from heat. Store in a well-ventilated place.
- Special rules on packaging : Store in a closed container.
- Packaging materials : Do not store in corrodable metal.

Switzerland

- Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	140 mg/m ³
	25 ppm
HTP (OEL STEL)	280 mg/m ³

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
	50 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	28 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	28 mg/m ³
	5 ppm
OEL STEL	112 mg/m ³
	20 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	168 mg/m ³
	30 ppm
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	140 mg/m ³
	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Allergenic substance
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	40 mg/m ³
	7 ppm
KZGW (OEL STEL)	80 mg/m ³
	14 ppm
OEL chemical category	Sensitizer
isobutyl acetate (110-19-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	241 mg/m ³ (Butyl acetates)
	50 ppm (Butyl acetates)
MAK (OEL STEL)	480 mg/m ³ (Butyl acetate)
	100 ppm (Butyl acetate)
Belgium - Occupational Exposure Limits	
OEL TWA	238 mg/m ³
	50 ppm
OEL STEL	712 mg/m ³

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isobutyl acetate (110-19-0)	
	150 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	241 mg/m ³
	50 ppm
KGVI (OEL STEL)	723 mg/m ³
	150 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	241 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA	241 mg/m ³ (Butyl acetate, all isomers)
	50 ppm (Butyl acetate, all isomers)
OEL STEL	723 mg/m ³
	150 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	240 mg/m ³ (Butyl acetate)
	50 ppm (Butyl acetate)
HTP (OEL STEL)	725 mg/m ³ (Butyl acetate)
	150 ppm (Butyl acetate)
France - Occupational Exposure Limits	
VME (OEL TWA)	241 mg/m ³ (restrictive limit)
	50 ppm (restrictive limit)
VLE (OEL C/STEL)	723 mg/m ³ (restrictive limit)
	150 ppm (restrictive limit)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isobutyl acetate (110-19-0)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	300 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	62 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	241 mg/m ³
CK (OEL STEL)	723 mg/m ³
OEL chemical category	Sensitizer
Ireland - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³ (calculated)
	150 ppm (calculated)
Italy - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	241 mg/m ³
	50 ppm
TPRV (OEL STEL)	723 mg/m ³
	150 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Malta - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isobutyl acetate (110-19-0)	
OEL STEL	723 mg/m ³
	150 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	241 mg/m ³
	50 ppm
TGG-15min (OEL STEL)	723 mg/m ³
	150 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³
NDSch (OEL STEL)	720 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	241 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	723 mg/m ³ (indicative limit value)
	150 ppm (indicative limit value)
Romania - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	241 mg/m ³
	50 ppm
NPHV (OEL C)	723 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	241 mg/m ³
	50 ppm
OEL STEL	723 mg/m ³
	150 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	241 mg/m ³
	50 ppm
VLA-EC (OEL STEL)	723 mg/m ³
	150 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	241 mg/m ³ (Butyl acetates)
	50 ppm (Butyl acetates)
KGV (OEL STEL)	723 mg/m ³ (Butyl acetates)
	150 ppm (Butyl acetates)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isobutyl acetate (110-19-0)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	724 mg/m ³
	150 ppm
WEL STEL (OEL STEL)	903 mg/m ³
	187 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	241 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	723 mg/m ³ (value from the regulation)
	150 ppm (value from the regulation)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	240 mg/m ³
	50 ppm
KZGW (OEL STEL)	720 mg/m ³
	150 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Butyl acetates, all isomers)
ACGIH OEL STEL	150 ppm (Butyl acetates, all isomers)
Butylated hydroxytoluene (BHT) crystals (128-37-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	10 mg/m ³
Belgium - Occupational Exposure Limits	
OEL TWA	2 mg/m ³ (aerosol and vapor)
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
OEL STEL	50 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	10 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	10 mg/m ³
HTP (OEL STEL)	20 mg/m ³
France - Occupational Exposure Limits	
VME (OEL TWA)	10 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	10 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-inhalable fraction)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Butylated hydroxytoluene (BHT) crystals (128-37-0)	
Greece - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	2 mg/m ³
OEL STEL	6 mg/m ³ (calculated)
Portugal - Occupational Exposure Limits	
OEL TWA	2 mg/m ³ (inhalable fraction; vapor)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Slovenia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (inhalable fraction)
OEL STEL	40 mg/m ³ (inhalable fraction)
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	10 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	10 mg/m ³
WEL STEL (OEL STEL)	30 mg/m ³ (calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	10 mg/m ³ (no elevated carcinogenic risk by keeping the MAK-value-aerosol, inhalable dust, vapour)
KZGW (OEL STEL)	40 mg/m ³ (no increased cancer risk by adhering to TWA values-aerosol, inhalable dust, vapour)
OEL chemical category	Category C1B carcinogen carcinogenic with threshold value
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	2 mg/m ³ (inhalable fraction and vapor)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³
	50 ppm
IOEL STEL	384 mg/m ³
	100 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
	50 ppm
MAK (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Skin notation

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m ³
	20 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	192 mg/m ³
	50 ppm
KGV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m ³
OEL chemical category	Potential for cutaneous absorption

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m ³
	25 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m ³
	25 ppm
HTP (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m ³ (restrictive limit)
	20 ppm (restrictive limit)
VLE (OEL C/STEL)	384 mg/m ³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	190 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: for long-term exposures: at the end of the shift after several shifts 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: end of shift
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190 mg/m ³
CK (OEL STEL)	384 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	1.6 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: end of shift
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m ³
	50 ppm
TPRV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m ³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m ³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	200 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ (indicative limit value)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
	50 ppm (indicative limit value)
OEL STEL	384 mg/m ³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m ³
	50 ppm
NPHV (OEL C)	384 mg/m ³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m ³
	50 ppm
KGV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m ³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m ³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
	50 ppm
KZGW (OEL STEL)	760 mg/m ³
	200 ppm
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 µmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 µmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 µg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m ³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m ³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m ³
	50 ppm
OEL STEL	618 mg/m ³

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m ³ (restrictive limit)
	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m ³ (isomer mixture)
	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
	100 ppm
OEL STEL	900 mg/m ³
	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (1-(3-Methoxypropoxy)propan-1-ol)
	50 ppm (1-(3-Methoxypropoxy)propan-1-ol)
OEL chemical category	skin - potential for cutaneous absorption

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSch (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL STEL	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m ³
	50 ppm
KGV (OEL STEL)	450 mg/m ³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)
isopentyl acetate (123-92-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	270 mg/m ³
	50 ppm

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
IOEL STEL	540 mg/m ³
	100 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	270 mg/m ³ (Pentyl acetate (all isomers))
	50 ppm (Pentyl acetate (all isomers))
MAK (OEL STEL)	540 mg/m ³ (Pentylacetate)
	100 ppm (Pentylacetate)
Belgium - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	270 mg/m ³
	50 ppm
KGVI (OEL STEL)	540 mg/m ³
	100 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Denmark - Occupational Exposure Limits	
OEL TWA	271 mg/m ³ (Amyl acetate, all isomers)
	50 ppm (Amyl acetate, all isomers)
OEL STEL	540 mg/m ³
	100 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	270 mg/m ³ (Pentyl acetate)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
	50 ppm (Pentyl acetate)
HTP (OEL STEL)	540 mg/m ³
	100 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	270 mg/m ³ (restrictive limit)
	50 ppm (restrictive limit)
VLE (OEL C/STEL)	540 mg/m ³ (restrictive limit)
	100 ppm (restrictive limit)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	270 mg/m ³
	50 ppm
Gibraltar - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Greece - Occupational Exposure Limits	
OEL TWA	530 mg/m ³
	100 ppm
OEL STEL	800 mg/m ³
	150 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	270 mg/m ³
CK (OEL STEL)	540 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	260 mg/m ³
	50 ppm
OEL STEL	520 mg/m ³
	100 ppm
Italy - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	270 mg/m ³

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
	50 ppm
TPRV (OEL STEL)	540 mg/m ³
	100 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Malta - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Netherlands - Occupational Exposure Limits	
TGG-15min (OEL STEL)	530 mg/m ³
	98.1 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	250 mg/m ³
NDSch (OEL STEL)	500 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	270 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value (Pentyl acetate, all isomers))
OEL STEL	540 mg/m ³ (indicative limit value)
	100 ppm (indicative limit value)
Romania - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	270 mg/m ³
	50 ppm
NPHV (OEL C)	540 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	270 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	540 mg/m ³
	100 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	270 mg/m ³ (Pentyl acetates)
	50 ppm (Pentyl acetates)
KGV (OEL STEL)	540 mg/m ³ (Pentyl acetates)
	100 ppm (Pentyl acetates)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	260 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	325 mg/m ³ (value calculated)
	75 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	260 mg/m ³ (Pentyl acetate all isomers)
	50 ppm (Pentyl acetate all isomers)
KZGW (OEL STEL)	260 mg/m ³ (Pentyl acetate all isomers)
	50 ppm (Pentyl acetate all isomers)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Pentyl acetate, all isomers)
ACGIH OEL STEL	100 ppm (Pentyl acetate, all isomers)
Diphenyl oxide (101-84-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	7 mg/m ³
	1 ppm
IOEL STEL	14 mg/m ³
	2 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	7 mg/m ³
	1 ppm
MAK (OEL STEL)	14 mg/m ³
	2 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	7 mg/m ³ (vapor)
	1 ppm (vapor)
OEL STEL	14 mg/m ³ (vapor)
	2 ppm (vapor)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	7 mg/m ³
	1 ppm
KGVI (OEL STEL)	14 mg/m ³
	2 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	7 mg/m ³
	1 ppm
HTP (OEL STEL)	14 mg/m ³
	2 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	7 mg/m ³ (indicative limit)
	1 ppm (indicative limit)
VLE (OEL C/STEL)	14 mg/m ³ (indicative limit)
	2 ppm (indicative limit)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	7.1 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor)
	1 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor)
Gibraltar - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	200 ppm
Greece - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	7 mg/m ³
CK (OEL STEL)	14 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	7 mg/m ³ (vapour)
	1 ppm (vapour)
OEL STEL	14 mg/m ³ (vapour)
	2 ppm (vapour)
Italy - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	7 mg/m ³
	1 ppm
TPRV (OEL STEL)	14 mg/m ³
	2 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Malta - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	7 mg/m ³
	1 ppm
TGG-15min (OEL STEL)	14 mg/m ³
	2 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	7 mg/m ³
NDSch (OEL STEL)	14 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	7 mg/m ³ (indicative limit value)
	1 ppm (indicative limit value-vapor)
OEL STEL	14 mg/m ³ (indicative limit value)
	2 ppm (indicative limit value-vapor)
Romania - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	7 mg/m ³
	1 ppm
NPHV (OEL C)	14 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	7.1 mg/m ³ (vapor)
	1 ppm (vapor)
VLA-EC (OEL STEL)	14.2 mg/m ³ (vapor)
	2 ppm (vapor)
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	7 mg/m ³

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
	1 ppm
KGV (OEL STEL)	14 mg/m ³
	2 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	7 mg/m ³
	1 ppm
WEL STEL (OEL STEL)	14 mg/m ³
	2 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	7 mg/m ³
	1 ppm
Korttidsverdi (OEL STEL)	14 mg/m ³ (value from the regulation)
	2 ppm (value from the regulation)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	7 mg/m ³ (aerosol, vapour)
	1 ppm (aerosol, vapour)
KZGW (OEL STEL)	14 mg/m ³ (aerosol, vapour)
	2 ppm (aerosol, vapour)
OEL chemical category	Category 2 reproductive toxin
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 ppm (vapor)
ACGIH OEL STEL	2 ppm (vapor fraction)
Amyl formate (638-49-3)	
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
TPRV (OEL STEL)	10 mg/m ³
OEL chemical category	Skin notation
Alcohol C-10 (112-30-1)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	66 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Alcohol C-10 (112-30-1)	
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	100 mg/m ³
	15 ppm
OEL STEL	200 mg/m ³
	30 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	66 mg/m ³ (aerosol, vapour)
	10 ppm (aerosol, vapour)
KZGW (OEL STEL)	66 mg/m ³ (aerosol, vapour)
	10 ppm (aerosol, vapour)
Aldehyde C-6 (66-25-1)	
Finland - Occupational Exposure Limits	
HTP (OEL STEL)	42 mg/m ³
	10 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	40 mg/m ³
NDSch (OEL STEL)	80 mg/m ³
Caproic acid (142-62-1)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
butyric acid (107-92-6)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
	4 ppm
OEL STEL	30 mg/m ³
	8 ppm

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask. [In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Conforms to standard.
Odour	: characteristic. characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Boiling point	: Not available
Flammability	: Combustible liquid, Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 66 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.007101996 mm Hg (calculated value)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 0.95
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 16.357135 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Sparks. Extremely high or low temperatures. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

May release flammable gases. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Verdorex (88-41-5)	
LD50 oral rat	4600 mg/kg (Source: NLM_CIP)
LD50 oral	4600 mg/kg

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Geranyl acetate (105-87-3)	
LD50 oral rat	6330 mg/kg (Source: NLM_CIP)
Eugenol (97-53-0)	
LD50 oral rat	1930 mg/kg (Source: NZ_CCID)
LD50 oral	2500 mg/kg bodyweight
LC50 Inhalation - Rat	> 2.58 mg/l/4h
Cinnamic aldehyde (104-55-2)	
LD50 oral rat	2220 mg/kg (Source: NLM_CIP)
LD50 oral	2220 mg/kg
LD50 dermal rabbit	1260 mg/kg (Source: EPA_HPVS)
Neryl acetate (141-12-8)	
LD50 oral rat	> 2000 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 6 ml/kg (Source: ECHA_API)
Citronellyl acetate (mixed Isomers) (150-84-5)	
LD50 oral rat	6800 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)
2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
LD50 oral rat	18500 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA)
Ethyl maltol (4940-11-8)	
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)
LD50 oral	1200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)
isobutyl acetate (110-19-0)	
LD50 oral rat	15400 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 17400 mg/kg (Source: NLM_CIP)
Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)
LD50 oral	3100 mg/kg bodyweight
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat	> 5 mg/l/4h
Ethylene brassylate (105-95-3)	
LD50 oral rat	> 5000 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Butylated hydroxytoluene (BHT) crystals (128-37-0)	
LD50 oral rat	> 2930 mg/kg (Source: EPA_HPVS)
LD50 dermal rat	> 2000 mg/kg (Source: JAPAN_GHS)
Triplal (Vertocitral) (68039-49-6)	
LD50 oral	2330 mg/kg
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
LD50 oral rat	2 g/kg (Source: NLM_CIP)
LD50 oral	2000 mg/kg bodyweight
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
Diphenyl oxide (101-84-8)	
LD50 oral rat	2450 mg/kg (Source: NLM_CIP)
LD50 oral	2830 mg/kg bodyweight
LD50 dermal rabbit	> 7940 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat (Dust/Mist)	1.5 mg/l/4h
Amyl formate (638-49-3)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)
COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
LD50 dermal rat	293 mg/kg (Source: ECHA_API)
benzyl benzoate (120-51-4)	
LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
Alcohol C-10 (112-30-1)	
LD50 oral rat	4720 mg/kg (Source: NZ_CCID)
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 71 mg/l (Exposure time: 1 h Source: ECHA_API)
Aldehyde C-6 (66-25-1)	
LD50 oral rat	4890 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 8100 mg/kg (Source: ECHA_API)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Caproic acid (142-62-1)	
LD50 oral rat	3 g/kg (Source: NLM_HSDB)
LD50 oral	4000 mg/kg bodyweight
LD50 dermal rabbit	630 mg/kg (Source: NLM_HSDB)
butyric acid (107-92-6)	
LD50 oral rat	2 g/kg (Source: NLM_CIP)
LD50 oral	1630 mg/kg bodyweight
LD50 dermal rabbit	530 mg/kg (Source: NLM_HSDB)
Skin corrosion/irritation	: Causes skin irritation.
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Eugenol (97-53-0)	
IARC group	3 - Not classifiable
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
IARC group	3 - Not classifiable
Butylated hydroxytoluene (BHT) crystals (128-37-0)	
IARC group	3 - Not classifiable
Toluene (108-88-3)	
IARC group	3 - Not classifiable
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
isobutyl acetate (110-19-0)	
STOT-single exposure	May cause drowsiness or dizziness.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Amyl formate (638-49-3)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Hydrocarbon	Yes
Toluene (108-88-3)	
Hydrocarbon	Yes
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.
Ecology - water : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Citronellyl acetate (mixed isomers) (150-84-5)	
LC50 - Fish [1]	6.1 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)
2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
LC50 - Fish [1]	569 mg/l 96 h
EC50 - Crustacea [1]	5.85 mg/l 48 h
EC50 - Other aquatic organisms [1]	5.94 mg/l 72 h
Ethyl maltol (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)
isobutyl acetate (110-19-0)	
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes Source: ECHA)
Butylated hydroxytoluene (BHT) crystals (128-37-0)	
EC50 72h - Algae [1]	6 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 72h - Algae [2]	> 0.42 mg/l (Species: Desmodesmus subspicatus)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)
Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
Alcohol C-10 (112-30-1)	
LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Aldehyde C-6 (66-25-1)	
LC50 - Fish [1]	12 – 16.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Caproic acid (142-62-1)	
LC50 - Fish [1]	306 – 334 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
butyric acid (107-92-6)	
EC50 72h - Algae [1]	46.7 mg/l (Species: Desmodesmus subspicatus)
12.2. Persistence and degradability	
Duftöl: Pear	
Persistence and degradability	May cause long-term adverse effects in the environment. Not established.
Verdox (88-41-5)	
Persistence and degradability	Rapidly degradable
Geranyl acetate (105-87-3)	
Persistence and degradability	Rapidly degradable
Eugenol (97-53-0)	
Persistence and degradability	Rapidly degradable

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Cinnamic aldehyde (104-55-2)	
Persistence and degradability	Rapidly degradable
Neryl acetate (141-12-8)	
Persistence and degradability	Rapidly degradable
Citronellyl acetate (mixed Isomers) (150-84-5)	
Persistence and degradability	Rapidly degradable
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Persistence and degradability	Rapidly degradable
2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
Persistence and degradability	Rapidly degradable
Ethyl maltol (4940-11-8)	
Persistence and degradability	Rapidly degradable
isobutyl acetate (110-19-0)	
Persistence and degradability	Rapidly degradable
Hexyl cinnamic aldehyde (101-86-0)	
Persistence and degradability	Rapidly degradable
Ethylene brassylate (105-95-3)	
Persistence and degradability	Rapidly degradable
Butylated hydroxytoluene (BHT) crystals (128-37-0)	
Persistence and degradability	Rapidly degradable
Triplal (Vertocitral) (68039-49-6)	
Persistence and degradability	Rapidly degradable
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
Persistence and degradability	Rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable
isopentyl acetate (123-92-2)	
Persistence and degradability	Rapidly degradable
Diphenyl oxide (101-84-8)	
Persistence and degradability	Rapidly degradable
Amyl formate (638-49-3)	
Persistence and degradability	Rapidly degradable
COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Alcohol C-10 (112-30-1)	
Persistence and degradability	Rapidly degradable
Aldehyde C-6 (66-25-1)	
Persistence and degradability	Rapidly degradable
Caproic acid (142-62-1)	
Persistence and degradability	Rapidly degradable
butyric acid (107-92-6)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
Duftöl: Pear	
Bioaccumulative potential	Not established.
Geranyl acetate (105-87-3)	
Partition coefficient n-octanol/water (Log Pow)	4.04
Eugenol (97-53-0)	
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5))
Cinnamic aldehyde (104-55-2)	
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)
Neryl acetate (141-12-8)	
Partition coefficient n-octanol/water (Log Pow)	3.98 (at 37 °C (at pH 7.2))
Citronellyl acetate (mixed Isomers) (150-84-5)	
Partition coefficient n-octanol/water (Log Pow)	4.9 (at 25 °C (at pH 4.23))
(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2))
2(3H)-Furanone, 5-heptyldihydro- (104-67-6)	
Partition coefficient n-octanol/water (Log Pow)	3.6 (at 25 °C)
Ethyl maltol (4940-11-8)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)
isobutyl acetate (110-19-0)	
BCF - Fish [1]	(no significant bioconcentration)
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7))
Ethylene brassylate (105-95-3)	
Partition coefficient n-octanol/water (Log Pow)	4.3 (at 25 °C (at pH 6.4-7))
Butylated hydroxytoluene (BHT) crystals (128-37-0)	
BCF - Fish [1]	230 – 2500

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Butylated hydroxytoluene (BHT) crystals (128-37-0)	
Partition coefficient n-octanol/water (Log Pow)	5.1
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 25 °C)
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)
isopentyl acetate (123-92-2)	
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)
Diphenyl oxide (101-84-8)	
BCF - Fish [1]	(470 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	4.21 (at 25 °C)
Amyl formate (638-49-3)	
Partition coefficient n-octanol/water (Log Pow)	2.786 (at 25 °C)
benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Alcohol C-10 (112-30-1)	
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 25 °C (at pH 6)
Aldehyde C-6 (66-25-1)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 5)
Caproic acid (142-62-1)	
Partition coefficient n-octanol/water (Log Pow)	1.88
butyric acid (107-92-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 (at 25 °C (at pH 3)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with local/national laws and regulations. Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecological information	: Avoid release to the environment.
HP Code	: HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(a)	(R)-p-mentha-1,8-diene; d-limonene; isobutyl acetate; Toluene; isopentyl acetate; Amyl formate; Aldehyde C-6	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Duftöl: Pear; Geranyl acetate; Eugenol; Cinnamic aldehyde; Neryl acetate; Citronellyl acetate (mixed Isomers); (R)-p-mentha-1,8-diene; d-limonene; isobutyl acetate; Hexyl cinnamic aldehyde; Triplal (Vertocitral); Toluene; Amyl formate; benzyl benzoate; Caproic acid; butyric acid	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Duftöl: Pear; Verdox; Geranyl acetate; Cinnamic aldehyde; Citronellyl acetate (mixed Isomers); (R)-p-mentha-1,8-diene; d-limonene; 2(3H)-Furanone, 5-heptyldihydro-; Hexyl cinnamic aldehyde; Ethylene brassylate; Triplal (Vertocitral); benzyl benzoate; Alcohol C-10	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	(R)-p-mentha-1,8-diene; d-limonene; isobutyl acetate; Toluene; isopentyl acetate; Amyl formate; Aldehyde C-6	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
48.	Toluene	Toluene

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 16.357135 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907.
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : Triplal (Vertocitral) is listed
SZW-lijst van mutagene stoffen : Triplal (Vertocitral) is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : Toluene is listed

Denmark

Class for fire hazard : Class III-1
Store unit : 50 liter
Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B

Duftöl: Pear

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.